



Quote Number: 393133 - 1
Altec, Inc.

September 28, 2017
Our 88th Year

Ship To:
CITY OF ALACHUA
13700 NW 126TH TER
ALACHUA, FL 32615
US

Bill To:
CITY OF ALACHUA
PO BOX 9
ALACHUA, FL 32615
United States

Attn:
Phone:
Email:

Altec Quotation Number: 393133 - 1
Account Manager: Bud Welch
Technical Sales & Support: Tyler Scott Hardie

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	<u>Unit</u>		
1.	Altec Model AT48M Articulating Telescopic Aerial Device with a fiberglass upper boom and fiberglass insulator in the articulating arm and proportional joystick upper controls. Built in accordance to ALTEC's standard specifications and to include the following features: <ul style="list-style-type: none">A. Ground to Bottom of Platform Height: 47.5 feet at 6.7 feet from centerline of rotation (14.48 m at 2.04 m)B. Working Height: 52.5 feet (16.00 m)C. Maximum reach to edge of platform with Upper Boom Non- overcenter: 31.2 feet (at 21.9 feet platform height)D. Upper boom extension: 110 inchesE. Continuous rotationF. Articulating Arm: Articulation is from -3 to 82 degrees. Insulator provides 19 inches of isolation.G. Compensation System: By raising the articulating arm only, the telescopic boom maintains its relative angle in relation to the ground. The work position is achieved through a single function operation.H. Upper Boom: Articulation is from -25 to 85 degrees. The fiberglass section provides a minimum of 33.1 inches of isolation in the upper boom (when retracted and 64.6 inches when extended)I. Platform leveling is achieved by a hydraulic master-slave leveling system. This lifetime system is very low maintenance.J. The dielectrically tested, insulating upper control system includes the following boom tip components that can provide an additional layer of secondary electrical contact protection. Control Handle: A single handle controller incorporating high electrical resistance components that is dielectrically tested to 40 kV AC with no more than 400 microampers of leakage. The control handle is green in color to differentiate it from other non-tested controllers. The handle also includes an interlock guard that reduces the potential for inadvertent boom operation. Auxiliary Control Covers: Non-tested blue silicon covers for auxiliary controls.	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	Control Console: Non-tested non-metallic control console plate. Boom Tip Covers: Non-tested non-metallic boom tip covers. The covers are not dielectrically tested, but they may provide some protection against electrical hazards.		
K.	Hydraulic system: Open center (full pressure), maximum flow 6 GPM, maximum operating pressure 3,000.		
L.	Dielectric rating: Category C, 46 kV and below		
M.	Unit is painted with a powder coat paint process which provides a finish-painted surface that is highly resistant to chipping, scratching, abrasion and corrosion. Paint is electrostatically applied to the inside as well as outside of fabricated parts then high temperature cured prior to assembly ensuring maximum coverage and protection.		
N.	Manuals: Two (2) Operator's and two (2) Maintenance/ Parts manuals containing instructional markings indicating hazards inherent in the operation of an aerial device.		
O.	Unit meets or exceeds ANSI 92.2 standards.		
2.	Pedestal	1	
3.	Single 1-Man Platform, Fiberglass (Insulated), 24" x 30" x 42", End Mount, 180 Degree Rotation	1	
4.	No Platform Elevator	1	
5.	Platform Mounted Single Handle Controls	1	
6.	Material Handling Jib/Winch, Hydraulically Articulating, Top Mounted, Round (ARM Jib)	1	
7.	Two(2) Platform steps - located on the side of the platform nearest the elbow in the stowed position	1	
8.	Platform Cover - soft vinyl, 24 x 30 inches (610 x 762 mm)	1	
9.	Platform Liner, 24 x 30 x 42 inches (610 x 762 x 1067 mm), 50 kV Rating	1	
10.	Hydraulic Tool Circuit at Platform: One set of quick disconnect couplings at the boom tip for open center tools.	1	
11.	Engine Start/Stop & Secondary Stowage System: 12 VDC powered motor and pump assembly for temporary operation of the unit in a situation wherein the primary hydraulic source fails. Electric motor is powered by the chassis battery. This feature allows the operator to completely stow the booms, platform, and outriggers. Secondary Stowage & Start/Stop is activated with an air plunger at the platform or momentary switch at the lower control station and outriggers.	1	
12.	Jib Stick, 36" L, non-extension, non certified, grey in color	1	
13.	Slip Ring: Required for engine start/stop, secondary stowage system, and throttle control options	1	
14.	Outriggers, Primary, Modified A-Frame, 30"-34" Chassis Height, Electric Interlock, No Valves On Legs, 112" Spread, Fixed Shoe	1	
15.	Auxiliary Vertical H Frame Outriggers, fixed shoe, provides 87 inch (2209 mm) maximum spread. Includes motion alarm and outrigger interlocks, which will not allow the unit to	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	be operated until the outriggers have been deployed. For installation on a 30 to 34 inch chassis frame height.		
16.	Electric Outrigger Controls, drive hydraulic outrigger control valves. Durable weather proof sealed electronic switches mounted in aluminum boxes located at the rear of the unit unless otherwise specified.	1	
17.	Winch load line swivel hook	1	
18.	Altec Aerial Device Powder Painted White	1	
<u>Unit & Hydraulic Acc.</u>			
19.	Scuff Pad, 24" x 30", With Step (For use with Platform Liner)	1	
20.	Subbase	1	
21.	Steel Reservoir, 15 gallon capacity, rectangular, 26" L x 8.5" W x 20" H, and includes breather caps and dipsticks	1	
22.	HVI-22 Hydraulic Oil (Standard).	25	
23.	Standard Pump For PTO	1	
24.	Electric Shifted PTO	1	
25.	Standard PTO/Transmission Functionality for Small Ford and Dodge Chassis	1	
<u>Body</u>			
26.	Altec LGSS-132-84 (81) Low-Side General Service Body With Step:	1	
A.	Steel Body		
B.	Steel Structural Channel Crossmembers And Smooth Floor With Ladder-Style Understructure		
C.	132" Body Length		
D.	94" Body Width		
E.	40" Body Compartment Height		
F.	20" Body Compartment Depth		
G.	24" From Body Floor To Compartment Tops		
H.	Finish Paint Entire Body Altec White		
I.	Undercoat Applied Under The Body		
J.	5.5" Drop-In Composite Cargo Retaining Board At Rear Of Body		
K.	5.5" Drop-In Composite Retaining Board At Top Of Side Access Step		
L.	Stainless Steel Rotary paddle Latches With Locks		
M.	Gas Props On All Vertical Doors		
N.	Chains On All Horizontal Doors		
O.	Standard Master Body Locking System		
P.	Hotstick Shelf Extending Full Length Of Body On Streetside		
R.	One Chock Holder On Each Side of Body With Retaining Lip In Fender Panel		
S.	1st Vertical (SS) - 34" W - One (1) Outrigger Housing And Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
T.	2nd Vertical (SS) - 24" W - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
U.	1st Horizontal (SS) - 50" W - One (1) Fixed Shelf With Removable Dividers On 4 Inch Centers On Bottom of Compartment		
V.	Rear Vertical (SS) - 24" W - Six (6) Locking Swivel Hooks On An Adjustable Rail (1-4-1)		
W.	1st Vertical (CS) - 34" W - One (1) Outrigger Housing And Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
X.	2nd Vertical (CS) - 24" W - Gripstrut Access Steps With Two (2) Sloped Grab Handles, Vented Battery Storage		
Y.	1st Horizontal (CS) - 50" W - One (1) Adjustable Shelf With Removable Dividers On 4 Inch Centers And One (1) Fixed Shelf With Removable Dividers On 4 Inch Centers On Bottom Of Compartment		
Z.	Rear Vertical (CS) - 24" W - Six (6) Locking Swivel Hooks On An Adjustable Rail (1-4-1)		
AA.	Body Floor Cut-Out For AT48M/P Aerial Device Near Center Of Body		
AB.	Steel Tailshelf, 29" L x 94" W, With Rear Cross Storage And Drop Down Doors		

Body and Chassis Accessories

27.	ICC (Underride Protection) Bumper Installed At Rear	1
28.	T-60 Style Pintle Hitch (10,000 LB MGTW with 2,000 LB MVL)	1
29.	Set Of Eye Bolts for Trailer Safety Chain, installed one each side of towing device mount.	1
30.	Rigid Step Mounted Beneath Side Access Steps (Installed To Extend Approx. 2" Outward)	1
31.	Platform Rest, Rigid with Rubber Tube	1
32.	Articulating Arm Rest for a Telescopic Unit	1
33.	Boom Rest for a Telescopic Unit	1
34.	Wood Outrigger Pad, 19" x 19" x 2.5", With Rope Handle	4
35.	Pendulum Retainers For Outrigger Pad Holders	2
36.	Custom Outrigger Pad Holder Outrigger Pad Holder, 20" L x 20" W x 7" H,	2
37.	Mud Flaps With Altec Logo (Pair)	1
38.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1
39.	Slope Indicator Assembly For Machine With Outriggers	1
40.	Safety Harness And 4.5' Lanyard (Fits Medium To Xlarge) Includes Pouch and Placards	1
41.	Driveaway Safety Kit	1
42.	Vinyl manual pouch for storage of all operator and parts manuals	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
<u>Electrical Accessories</u>			
43.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1	
44.	Altec Standard Amber LED Strobe Light with Brush Guard One (1) each side, installed on post at the front of the body	2	
45.	4-Corner Strobes, Amber, LED, Two (2) Surface Mounted Lights In Grille, Two (2) Round Lights At Rear	1	
46.	Dual Tone Back-Up With Outrigger Motion Alarm	1	
47.	PTO Hour Meter, Digital, with 10,000 Hour Display	1	
48.	6-Way Trailer Receptacle (Pin Type) Installed At Rear	1	
49.	Electric Trailer Brake Controller (Tekonsha Voyager #9030)	1	
50.	Ford Upfitter Switches (Supplied With Chassis)	1	
51.	Start/Stop/Throttle Module, 12 Volt System	1	
52.	Install secondary stowage system.	1	
53.	Install Remote Start/Stop system in Final Assembly.	1	
54.	Install Outrigger Interlock System	1	
55.	Standard Duty Secondary Stowage Pump	1	
56.	PTO Indicator Light Installed In Cab	1	
<u>Finishing Details</u>			
57.	Powder Coat Unit Altec White	1	
58.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1	
59.	Apply Non-Skid Coating to all walking surfaces	1	
60.	English Safety And Instructional Decals	1	
61.	Vehicle Height Placard - Installed In Cab	1	
62.	Placard, HVI-22 Hydraulic Oil	1	
63.	Dielectric test unit according to ANSI requirements.	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
64.	Stability test unit according to ANSI requirements.	1	
65.	Focus Factory Build	1	
66.	Delivery Of Completed Unit	1	
67.	Inbound Freight	1	
68.	Installation - AT48M	1	
69.	Stock Unit	1	
<u>Chassis</u>			
70.	Chassis	1	
71.	Altec Supplied Chassis	1	
72.	2017 Model Year	1	
73.	Ford F550	1	
74.	4x4	1	
75.	84 Clear CA (Round To Next Whole Number)	1	
76.	Regular Cab	1	
77.	Chassis Cab	1	
78.	Chassis Color - White	1	
79.	Chassis Wheelbase Length - 169	1	
80.	Ford 6.7L Power Stroke Diesel	1	
81.	Ford Torqshift 6-Speed (6R140) Automatic Transmission (w/PTO Provision)	1	
82.	GVWR 19,500 LBS	1	
83.	7,500 LBS Front GAWR	1	
84.	14,706 LBS Rear GAWR	1	
85.	225/70R19.5 Front Tire (Traction)	1	
86.	225/70R19.5 Rear Tire (Traction)	1	
87.	Hydraulic Brakes	1	
88.	Park Brake In Rear Wheels	1	
89.	Ford E/F250-550 Single Horizontal Right Side Exhaust	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
90.	63C - Aft Axle Frame Extension	1	
91.	98R - Operator Commanded Regeneration (OCR)	1	
92.	No Idle Engine Shut-Down Required	1	
93.	50-State Emissions	1	
94.	Clean Idle Certification	1	
95.	Ford 40 Gallon Fuel Tank (Rear)	1	
96.	Ford 7.2 Gallon DEF Tank (Mid Mount)	1	
97.	AM/FM Radio	1	
98.	Air Conditioning	1	
99.	Cruise Control	1	
100.	Tilt Steering Wheel	1	
101.	Block Heater	1	
102.	Vinyl Split Bench Seat	1	

Additional Pricing

103.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1	
------	---	---	--

Unit / Body / Chassis Total	136,989.00
FET Total	0.00
Total	136,989.00

Altec Industries, Inc.

BY

Tyler Scott Hardie

Notes:

- 1 Altec Standard Warranty:
One (1) year parts warranty.

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

One (1) year labor warranty.

Ninety (90) days warranty for travel charges.

Warranty on structural integrity of the following major components is to be warranted for so long as the initial purchaser owns the product: Booms, boom articulation links, hydraulic cylinder structures, outrigger weldments, pedestals, subbases and turntables.

Altec is to supply a self-directed, computer based training (CBT) program. This program will provide basic instruction in the safe operation of this aerial device. This program will also include and explain ANSI and OSHA requirements related to the proper use and operation of this unit.

Altec offers its standard limited warranty with the Altec supplied components which make up the Altec Unit and its installation, but expressly disclaims any and all warranties, liabilities, and responsibilities, including any implied warranties of fitness for a particular purpose and merchantability, for any customer supplied parts

Altec designs and manufactures to applicable Federal Motor Vehicle Safety and DOT standards

- 2 Altec takes pride in offering solutions that provide a safer work environment for our customers. In an effort to focus on safety, we would encourage you to consider the following items:

Outrigger pads (When Applicable)
Fall Protection System
Fire extinguisher/DOT kit
Platform Liner (When Applicable)
Altec Sentry Training
Wheel Chocks

The aforementioned equipment can be offered in our new equipment quotations. If you find that any of these items have not been listed as priced options in the body of your quotation and are required by your company, we would encourage you to contact your Altec Account Manager and have an updated quotation developed for you. These options must be listed as individual options in the body of the quotation for them to be supplied by Altec.

- 3 Altec Extended Warranty Option:

Labor/Material/Expense for 1 Year. Price to be quoted

An Altec Extended Warranty is an extension of Altec's Limited Warranty, that protects you from the repair cost associated with defects of materials and workmanship beyond the first year of ownership.

A number of packages are available and can be quoted upon request.

- 4 Unless otherwise noted, all measurements used in this quote are based on a 40 inch (1016mm) chassis frame height and standard cab height for standard configurations.

- 5 F.O.B. - Customer Site

- 6 Changes made to this order may affect whether or not this vehicle is subject to F.E.T. A review will be made at the time of invoicing and any applicable F.E.T. will be added to the invoice amount.

- 7 Price does not reflect any local, state or Federal Excise Taxes (F.E.T). The quote also does not reflect any local title or licensing fees. All appropriate taxes will be added to the final price in accordance with regulations in effect at time of invoicing.

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

- 8 Interest charge of 1/2% per month to be added for late payment.
- 9 Delivery: Contingent on availability of selected stock unit(s).
- 10 Trade-in offer is conditional upon equipment being maintained to DOT (Department of Transportation) operating and safety standards. This will include, but is not limited to tires, lights, brakes, glass, etc. All equipment, i.e., jibs, winches, pintle hooks, trailer connectors, etc., are to remain with unit unless otherwise agreed upon in writing by both parties. ALTEC Industries reserves the right to re-negotiate its trade-in offer if these conditions are not met.
- All reasonable and necessary expenses required of ALTEC Industries to execute transportation of the trade-in will be invoiced to the customer for payment if these conditions are not met to maintain DOT standards.
- Customer may exercise the option to rescind this agreement in writing within sixty (60) days after receipt of purchase order. After that time ALTEC Industries will expect receipt of trade-in vehicle upon delivery of new equipment as part of the terms of the purchase order unless other arrangements have been made.
- 11 This quotation is valid until DEC 07, 2017. After this date, please contact Altec Industries, Inc. for a possible extension.
- 12 After the initial warranty period, Altec Industries, Inc. offers mobile service units, in-shop service and same day parts shipments on most parts from service locations nationwide at an additional competitive labor and parts rate. Call 877-GO-ALTEC for all of your Parts and Service needs.
- 13 Please email Altec Capital at finance@altec.com or call 888-408-8148 for a lease quote today.
- 14 Please direct all questions to Bud Welch at (205) 323 8751



Opportunity Number: 799286
 Quotation Number: 393133
 NJPA Contract #: 031014-ALT
 Date:

Quoted for: City of Alachua
 Customer Contact:
 Phone: /Fax: /Email:
 Quoted by: Tyler Hardie
 Phone: /Fax: /Email: 816-676-4023
 Altec Account Manager: Bud Welch

REFERENCE ALTEC MODEL

AT41M	Articulating Telescopic Aerial Device with Material Handling (Insulated)	\$116,990
-------	--	-----------

(A.) NJPA OPTIONS ON CONTRACT (Unit)

1	AT48M	\$12,117
2	AT41M-AWD	\$5,069
3		
4		
5		
6		

(A1.) NJPA OPTIONS ON CONTRACT (General)

1	SPOT3	FOUR (4) POINT STROBE SYSTEM (Recessed, LED)	\$477
2			
3			
4			
5			
6			
7			
8			

NJPA OPTIONS TOTAL: \$134,653

(B.) OPEN MARKET ITEMS (Customer Requested)

1	UNIT		
2	UNIT & HYDRAULIC ACC		
3	BODY		
4	BODY & CHASSIS ACC		
5	ELECTRICAL		
6	FINISHING		
7	CHASSIS		
8	OTHER		

OPEN MARKET OPTIONS TOTAL: \$0

SUB-TOTAL FOR UNIT/BODY/CHASSIS: \$134,653

Delivery to Customer: \$2,336

TOTAL FOR UNIT/BODY/CHASSIS: \$136,989

(C.) ADDITIONAL ITEMS (items are not included in total above)

1			
2			
3			
4			

****Pricing valid for 45 days****

NOTES

PAINT COLOR: White to match chassis, unless otherwise specified

WARRANTY: Standard Altec Warranty - One (1) year parts warranty One (1) year labor warranty Ninety (90) days warranty for travel charges (Mobile Service) Limited Lifetime Structural Warranty. Chassis to include standard warranty, per the manufacturer. (Parts only warranty on mounted equipment for overseas customers)

TO ORDER: To order, please contact the Altec Inside Sales Representative listed above.

CHASSIS: Per Altec Commercial Standard

DELIVERY: No later than 270-300 days ARO, FOB Customer Location

TERMS: Net 30 days

BEST VALUE: Altec boasts the following "Best Value" features: Altec ISO Grip Controls for Extra Protection, Only Lifetime Warranty on Structural Components in Industry, Largest Service Network in Industry (Domestic and Overseas), Altec SENTRY Web/CD Based Training, Dedicated/Direct Gov't Sales Manager, In-Service Training with Every Order.

TRADE-IN: Equipment trades must be received in operational condition (as initial inspection) and DOT compliant at the time of pick-up. Failure to comply with these requirements, may result in customer bill-back repairs.

BUILD LOCATION: Saint Joseph, MO

Customer				Service Request	
Estimate #	343073			Service Request #	3032726
Customer	ALTEC			Unit Information	
Account #	70274	Payment Terms	IMMEDIATE	Customer Vehicle #	
Contact	WARREN WELCH			Model	AT48M
Email				Chassis VIN #	1FDUF5HT6HDA06817
Phone	561-301-1066	Fax		Mileage	
Mobile				Unit Serial #	0717GH0628
Altec Representative				Assy Serial # (FA)	027-47386856
Contact	David L. Banks			In-Service Date	
Email	David.Banks@altec.com				
Phone		Fax			
This Estimate Expires: 20-JAN-2018					
Notes:					

Item	Description	Hours	Labor	Material	Expenses	Total
1	INSTALL 12000 LBS ELECTRIC WARN WINCH AND HIDDEN WINCH MOUNT FRONT BUMPER	10.00	\$1,010.00	\$3,384.82	\$0.00	\$4,394.82
2	INSTALL ALTEC BACKUP CAMERA SYSTEM WITH LCD MONITOR, HEAT AND INFRARED.	6.00	\$606.00	\$766.93	\$0.00	\$1,372.93
3	OPERATIONAL TEST, MAKE LENS ANGLE ADJUSTMENTS	0.50	\$50.50	\$0.00	\$0.00	\$50.50
4	INSTALL 2500 W INVERTER TO 1ST CURBSIDE VERTICAL COMPARTMENT	6.00	\$606.00	\$2,101.24	\$0.00	\$2,707.24
5	INSTALL SWITCH ON DASH FOR REMOTE OPERATION	2.00	\$202.00	\$24.23	\$0.00	\$226.23
6	INSTALL (1) RECEPTACLE IN CAB OR OTHER LOCATION ON BODY	2.00	\$202.00	\$128.36	\$0.00	\$330.36
7	~INSTALL ROPE LIGHT IN ALL BODY COMPARTMENTS	10.00	\$1,010.00	\$674.16	\$0.00	\$1,684.16
8	INSTALL METAL LADDER BOX ON TOP OF STREETSIDE BODY	2.00	\$202.00	\$0.00	\$2,250.00	\$2,452.00
9	INSTALL 30"x18"x12" BOX ON TOP OF LADDER BOX AT FRONT OF BODY	2.00	\$202.00	\$774.44	\$0.00	\$976.44
10	INSTALL 3" LIP SURROUNDING TOP OF LADDER BOX	2.00	\$202.00	\$0.00	\$55.50	\$257.50
11	INSTALL GO LIGHT ON CURBSIDE OF HOOD	2.00	\$202.00	\$580.30	\$0.00	\$782.30
12	INSTALL ELECTRIC TRAILER BRAKE CONTROLLER	4.00	\$404.00	\$107.88	\$30.50	\$542.38
13	INSTALL (2) FLOOD LIGHTS ON EACH SIDE OF BODY AND (1) AT REAR	4.00	\$404.00	\$420.96	\$91.50	\$916.46
14	INSTALL TRANSFORMER BRACKET ON STREETSIDE REAR OF TAILSHELF	2.00	\$202.00	\$0.00	\$277.50	\$479.50
15	INSTALL RUBBER GOODS BOX ON TOP OF CURBSIDE BODY AT REAR	2.00	\$202.00	\$2,381.79	\$0.00	\$2,583.79
16	INSTALL BICYCLE STYLE WIRE HOLDER INSIDE CARGO AREA NEAR STREETSIDE BULKHEAD	2.00	\$202.00	\$438.92	\$0.00	\$640.92
17	INSTALL (2) PVC TUBES WITH CAPS INSIDE CARGO WALL ON STREETSIDE REAR FLUSH WITH REAR OF BODY	3.00	\$303.00	\$191.02	\$35.00	\$529.02
18	INSTALL WIRE HOLDER UNDER CURBSIDE TAILSHELF	1.00	\$101.00	\$438.92	\$0.00	\$539.92
19	INSTALL CONE HOLDER ON STREETSIDE OF TAILSHELF	1.00	\$101.00	\$517.37	\$0.00	\$618.37
20	FREIGHT ESTIMATE	0.00	\$0.00	\$0.00	\$1,050.00	\$1,050.00
21	ENVIRONMENTAL DISPOSAL FEE/SHOP SUPPLIES	0.00	\$0.00	\$0.00	\$355.00	\$355.00
Totals		63.50	\$6,413.50	\$12,931.34	\$4,145.00	\$23,489.84

*This estimate is provided with the understanding that items may be discovered during the repair process that may require additional labor and/or materials to repair. Examples would include, but are not limited to, hidden damages or items that were not clearly visible or known at the time of estimate, damaged internal components, fasteners and pins that may be rusted, seized or broken.

**This estimate does not include City, County, State or Federal taxes.

***Transportation or towing of the vehicle is not included in the estimate unless specified.

****Freight charges are estimated and may be adjusted to reflect the actual cost incurred on the invoice.

Please sign below to authorize this estimate			
Printed Name:	P.O.		Date:
Signature:			Would you like to keep salvageable parts removed from the unit?
			Yes No

Altec Service Group Limited Warranty

Products rebuilt or repaired by Altec Service Group are warranted to be free from defects in material and workmanship at the time of rebuild/repair subject to the following provisions:

- § Labor Coverage: For a period of six (6) months following the date of repair, no charge for labor shall be made for a repair or replacement by the Altec Service Group.
- § Travel Coverage: For a period of thirty (30) days following the date of repair, no charge for travel shall be made for a repair or replacement at the customers location by the Altec Service Group.
- § Parts Coverage: For a period of one (1) year following the date of repair, Altec will at its option, repair or replace any part found to be defective in material or workmanship at the time of repair.
- § This warranty is limited to parts that are repaired or replaced by the Altec Service Group. Authorization and coverage of this warranty will be at the discretion of the Altec Service Group.
- § Accessory items are excluded from this warranty and will be warranted from the original manufacturer.

This limited warranty is expressly in lieu of any other warranties, express or implied, including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Except as specified above, no associate, agent or representative of Altec is authorized to extend any warranty on Altec's behalf. Remedies under this limited warranty are expressly limited to the provision and installation of parts and labor, as specified above, and any claims for other loss or damages of any type (including, but not limited to, loss from failure of the product to operate for any period of time, other economic or moral loss, or direct, immediate, special, indirect, incidental or consequential damage) are expressly excluded.

Ser War 2-10 Altec Industries, Inc.